MAGICCLEANER

/ Cleaning CrNi



/ MagicCleaner is the quick and easy electrochemical way to clean CrNi sheets and pipes. Small, compactly built and weighing only 5 kg, the device is ideal for use in the field and in any workshop. It cleans TIG weld-seams quickly and thoroughly using microprocessor-controlled current waveforms. The integral burnishing function lets you polish the surfaces to a lustrous finish after they have been cleaned.

FACTS

- / Electrolyte-feed integrated in the cleaning stylus
- / Automatic and manual liquid-feed modes
- / Special cleaning cloth for extra-long service life
- / Optimised cleaning process for 28 % faster cleaning speed
- / Automatic short-circuit detection
- / Processor-controlled safety cut-out prevents damage to workpiece and triangle

Mains voltage 230V 50/60Hz Nominal power 300 W Cleaning-current range 5 - 20 A Open-circuit voltage 15 V Working voltage 5 - 15 V Electrolyte delivery rate 0.55 - 2.2 l/h Cleaning time 2.2 l/h / 40 min Cleaning-fluid reservoir 1.5 l IEC 'degree of protection' code IP 23 Dimensions LxWxH 430x180x280 mm (16.9x7.1x11.0 in)	TECHNICAL DATA	
Cleaning-current range 5 - 20 A	Mains voltage	230V 50/60Hz
Open-circuit voltage 15 V Working voltage 5 - 15 V Electrolyte delivery rate 0.55 - 2.2 l/h Cleaning time 2.2 l/h / 40 min Cleaning-fluid reservoir 1.5 l IEC 'degree of protection' code IP 23 Dimensions LxWxH 430x180x280 mm (16.9x7.1x11.0 in)	Nominal power	300 W
Working voltage	Cleaning-current range	5 - 20 A
Electrolyte delivery rate	Open-circuit voltage	15 V
Cleaning time 2.2 l/h / 40 min 0.55 l/h / 160 min Cleaning-fluid reservoir 1.5 l IEC 'degree of protection' code IP 23 Dimensions LxWxH 430x180x280 mm (16.9x7.1x11.0 in)	Working voltage	5 - 15 V
Cleaning time	Electrolyte delivery rate	0.55 - 2.2 l/h
IEC 'degree of protection' code IP 23 Dimensions LxWxH 430x180x280 mm (16.9x7.1x11.0 in)	Cleaning time	
Dimensions LxWxH 430x180x280 mm (16.9x7.1x11.0 in)	Cleaning-fluid reservoir	1.5 l
Dimensions LxWxH (16.9x7.1x11.0 in)	IEC 'degree of protection' code	IP 23
	Dimensions LxWxH	
Weight 5 kg (11.0 lbs)	Weight	5 kg (11.0 lbs)



/ after cleaning



/ after burnishing / 1

/ Electrolyte-feed integrated in cleaning stylus; flow-rate is precisely dosed in either manual or automatic feed mode.

Fronius Canada Ltd.

2875 Argentia Road, Units 4,5 & 6 Mississauga, ON L5N 8G6 Canada

/ CrNi before cleaning

Telephone +1 905 288-2100 Fax +1 905 288-2101 sales.canada@fronius.com Fronius USA LLC 6797 Fronius Drive Portage, IN 46368

Telephone +1 877 FRONIUS sales.usa@fronius.com www.fronius-usa.com Fronius UK Limited

Maidstone Road, Kingston Milton Keynes, MK10 0BD United Kingdom Telephone +44 1908 512 300 Fax +44 1908 512 329 info-uk@fronius.com www.fronius.co.uk Fronius International GmbH

Froniusplatz 1
4600 Wels
Austria
Telephone +43 7242 241-0
Fax +43 7242 241-953940
sales@fronius.com
www.fronius.com