

The new

# MULTIBAY CHARGER E3000-SERIES



 **optrel**<sup>®</sup>  
swiss made 

SEE  
WHAT YOU  
CAN DO

# ORGANISED ENERGY MANAGEMENT FOR YOUR COMPANY

## CONTINUOUS WORKFLOW

Six charging cradles for simultaneous charging of up to 6 batteries. Always at hand for uninterrupted use of the optrel e3000 / e3000X.

## ORGANISED ENERGY MANAGEMENT

Simplifies the administration and maintenance of the batteries. The batteries always have a fixed place during recharging. They are also protected from accidentally falling.

## NO MORE CABLE CLUTTER

The optrel multibaycharger increases the overview and reduces the risk of trip hazards caused by individual charging cables at the workplace.

## SMART CONSTRUCTION





The lack of a socket and storage space are a thing of the past. The robust aluminium multi-charging station can be freely attached to any surface or optionally by wall mounting.

## LED DISPLAY

A charge indicator for each battery clearly shows the charge status of all batteries.

## COMPATIBLE

Compatible with all batteries of the e3000 and e3000X models.

Description	Art. No.	Description	Art. No.
 <b>multibaycharger e3000-Series CH-device power cord</b> 1 piece	4551.015.CH	 <b>multibaycharger e3000-Series UK-device power cord</b> 1 piece	4551.017.UK
 <b>multibaycharger e3000-Series EU-device power cord</b> 1 piece	4551.016.EU	 <b>multibaycharger e3000-Series US-device power cord</b> 1 piece	4551.018.US

**Description**  
Robust multi-charging station for simultaneous charging of up to six batteries of all models of the e3000-Series.  
Full compatibility with all battery models of the e3000 and e3000X models.  
Charge indicator for each individual battery.  
Six separate storage recesses for the batteries.  
As a stand-alone device or suitable for wall mounting. Shapely and stable aluminum housing. Power cord included.

**Case material** Aluminium

**Colour** White aluminium matt

**Charging ports** 6 x 16,8V 1000mA

**LED charge indicator** Red: battery empty and charging,  
Green: battery full or not connected

**Power supply** 100-230V / 50/60Hz max. 3.6A

**Fuse** 5x20mm, 1,6A

**Power consumption** max. 900W

**Operating temperature** 0°C to +45°C  
+32 °F to +113 °F

**Storage temperature** -30°C to +70°C  
-22 °F to +158 °F

**Humidity** 10% to 90% relative humidity

**IP Class** IP30

**Protection class** 1

**Weight** 2'370g

**Dimensions WxDxH** 525mm x 240mm x 160mm

**Areas of application** Suitable for all e3000 and e3000X batteries

**Scope of delivery** multibaycharger 3000-Series, power cord according to order number, operating instructions

**Warranty** 2 years from the date of sale (on manufacturing and material defects)