

CETO 2 WELDING BLANKET

Description

Ceto 2 is a Glass fabric with silicone rubber coating on both sides.

Application

The maximum application temperature is 550 °C, shortly up to 600°C.

Conditions for use

- CEPRO recommends the use of multiple layers for maximum protection.
- Always use welding blankets at an angle of at least 15 degrees.
- The temperatures shown are only an indication. The suitability of the selected product should always be tested beforehand.
- Regularly check welding blankets for tears and or other damage. Replace damaged blankets where necessary.
- Welding blankets can be used for many purposes and therefore, no guarantee can be given on their use. The end user is responsible for determining whether the welding blanket is suitable for use in a specific situation and whether it offers sufficient protection during the work to be performed.
- CEPRO welding blankets are sewn on the cut edges with best quality Kevlar thread.

Characteristics

Ceto 2 has a silicone coating with silicone rubber, high resistance to extreme mechanical, thermal and electric influence.

- good light stability, UV resistance and resistance to oxidation
 - mostly resistance to acids and lyes
 - weatherproof
 - good soil-repellent and oil-repellent properties
 - good electrical insulation properties
- Ceto 2 is free of asbestos.

Available dimensions

Full roll 25 m¹, width 100 cm 56.52.06.1025
Ready made blankets can be made on request.

