



AKFH 18-5 AS

Cordless beveller up to 5 mm

Powerful cordless beveller for perfectly preparing subsequent coatings for flexible jobs in the workshop and on the construction site.

Product number: 7 138 02 62 00 0

Details

- + For the production of bevels and radii on flat materials, sheet metals and containers, of inner and outer edges, contour shapes and for rounding off holes.
- + High sanding capacity requiring little force and infinitely variable speed setting for different materials.
- + Ergonomic thanks to low weight and compact design.
- + FEIN PowerDrive motor delivers good performance and long service life.
- + Extensive user protection features include soft start, restart protection, jam monitoring and electronic overload protection.
- + Compatible with all 18 V AMPShare ProCORE batteries and chargers for even more power and flexibility. Also suitable for 18 V Bosch Professional cordless devices.
- + ProCORE Li-Ion battery with high-power cells, charge status indicator and "Electronic Cell Protection" (ECP). ECP protects against overload, overheating and total discharge.
- + COOLPACK 2.0 technology delivers a 135% longer battery life and therefore makes longer operating times possible.
- + Extensive range of accessories for various materials such as steel, stainless steel and non-ferrous metals.
- + Above-average service life of the indexable inserts due to 8-fold or 16-fold usability.
- + Ideally equipped for every job. Mobile working with the L-BOXX system.

Price includes

- + 1 tool incl. 45 milling head (without guide roller, without indexable tips)
- + 1 x copper paste
- + 1 x TX 15 Torx screwdriver
- + 3 x clamping screws SX
- + 1 x 4 mm socket head wrench
- + 1 plastic tool case (L-BOXX 238)

Product feature

- + Soft start
- + Blockage monitoring
- + Speed preselection
- + Restart protection
- + Electronic overload protection

Application

Installation work

++

Bevel length of up to 5 mm at 45°

+

Workshop jobs

+

+ suitable
++ well suitable

Technical data

TECHNICAL DATA

Battery voltage

18 V

Battery compatibility

Li-ion / ProCORE Li-ion

Battery interface

18 V AMPShare

Speed, no load

2,400 - 7,500 rpm

Max. bevel length at 45°

5 mm

Max. bevel height at 45°

3.5 mm

Bevel angle

45°

Radius

1.2 / 2,5 mm

Milling head configuration

3x SX tip

Support plate diameter

98 mm

Weight without storage battery

2.52 kg

VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA
Uncertainty of measured value
KpA

85 dB
3 dB

Sound power level LWA
Uncertainty of measured value
KWA

96 dB
3 dB

Sound peak value
LpCpeak
Uncertainty of measured value
KpCpeak

100 dB
3 dB

Vibration value 1 α_{hv} 3-way
Vibration value 2 α_{hv} 3-way

3,1 m/s²
4,5 m/s²

Uncertainty of measured value
K α

1,5 m/s²

Application examples

