

SLICE® Striker Assembly

Striker assembly is used to complete the ignition circuit to establish the exothermic burn from a 12 V battery power source



SLICE Striker Assembly

Go anywhere and cut, burn, or pierce virtually any metallic, non-metallic or composite material with SLICE exothermic cutting equipment.

The SLICE Striker comes standard with a #10 AWG Power Cable with a twist-lock brass pin that can connect to the SLICE battery ignition source. The same twist-lock pin can be inserted into the mating receptacle on a plier type clamp found in the SLICE Utility Pack (please see separate fact sheet for details).

- Improved striker assembly that incorporates a slide mechanism that allows the operator to only expose a small portion of the ignition bar (copper) which increases the life of the striker copper bar
- Robust handle insulator material that can handle impact with the ground and high temperature rating

Visit esab.com for more information.

Industry

- Repair & Maintenance
- Salvage
- Mining
- Steel Erectors
- Earth Moving Excavating
- Industrial & general fabrication

Specifications

| | |
|-------------------------------------|---|
| Length Of Power Cable & Oxygen Hose | 3 m (10 ft.) |
| Power Cable AWG Size | #10 AWG |
| Certification Mark (Standards) | CE |
| Dimensions L x W x H | 9.5 in. x 1.5 in. x 1.75 in. (241.3 mm x 38.1 mm x 44.5 mm) |
| Weight | 1.2 lbs (.54 kg) |

Ordering Information

| | |
|------------------------|------------|
| SLICE Striker Assembly | 72-012-010 |
|------------------------|------------|



ESAB / esab.com

