



KBU 110-4 M

Universal magnetic core drill for up to 110 mm

High-performance and powerful 4-speed universal magnetic core drill with forward/reverse running, MT4 tool mounting and maximum functionality for the toughest drilling jobs in the workshop.

Product number: 7 270 60 61 00 0

Details

- + FEIN 1700 W high-power motor with high torque for heavy-duty drilling work.
- + For tough use thanks to outstanding quality of workmanship and swivel-mounted motor cable protective hose.
- + Tool with extra large stroke range for all drilling work, such as core, twist and tap drilling, countersinking and reaming.
- + Mechanical 4-speed gearbox.
- + High magnetic holding force.
- + Torque support for high stability.
- + Tilt sensor.
- + Slipping clutch torque.
- + Convenient magnetic holding force display helps the user to reliably position the tool.
- + Speed reduction.
- + Reversible.
- + MT4 tool mounting.
- + Integrated coolant tank delivers long core drill bit lives.
- + Personal safety switch.

Price includes

- + 1 coolant tank
- + 1 swarf hook
- + 1 contact guard
- + 2 x 5 and 6 mm hexagon socket wrench
- + 1 case
- + 1 safety strap with ratchet
- + 2 centring pins, diameter of 6.35 x 125 mm and diameter of 7.98 x 184 mm
- + 1 drift key
- + 1 additional handle

Product feature

- + Magnetic holding force display
- + Variable speed control
- + Tilt sensor
- + Reversible rotation
- + Torque slipping clutch

Application

- Core drilling in metal with a Ø up to 35 mm
- Core drilling in metal with a Ø up to 50 mm
- Core drilling in metal with a Ø up to 65 mm
- Core drilling in metal with a Ø up to 110 mm





Twist drills with drill chuck (DIN 338)	++
Twist drills with MK fitting (DIN 345)	++
Tapping	++
Countersinking	++
Reaming	++
Working overhead	+
Installation work	+
Workshop jobs	++

+ suitable
 ++ well suitable

Technical data

TECHNICAL DATA

Input	1,700 W
Output	850 W
Load speed in speed 1	60 / 120 rpm
Load speed in speed 2	90 / 170 rpm
Load speed in speed 3	150 / 300 rpm
Load speed in speed 4	230 / 430 rpm
Idling speed in speed 1	100 / 190 rpm
Idling speed in speed 2	160 / 290 rpm
Idling speed in speed 3	270 / 500 rpm
Idling speed in speed 4	420 / 750 rpm

VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA Uncertainty of measured value KpA	86,0 dB 5 dB
Sound power level LWA Uncertainty of measured value KWA	97,0 dB 5 dB
Sound peak value LpCpeak Uncertainty of measured value KpCpeak	98,5 dB 5 dB
Vibration value 1 α_{hv} 3-way Uncertainty of measured value K α	ah,D = 1,4 m/s ² 1,5 m/s ²

Tool Holder	MK 4
Carbide core drill bit max. Ø	110 mm
HSS core drill max. Ø	80 mm
Core drill, drilling depth max.	100 mm
Twist drill max. Ø	40 mm
Tapping	M 36
Countersinking max. Ø	60 mm
Reaming max. Ø	36 mm
Core drill holder	Weldon 32
Stroke	280 mm
Total stroke range	400 mm
Magnetic holding power	23,000 N
Cable with plug	4 m
Weight according to EPTA	35.00 kg
Weight according to EPTA	35.00 kg

Application examples



Zahnbohrerschleife 120-A-M
 Schleife durch Verschieben der 800-PWM-Drillbohrmaschine auf die horizontale 100-A-M-Drillbohrmaschine
 Schleife durch Verschieben der 100-A-M-Drillbohrmaschine auf die 800-PWM-Drillbohrmaschine
 Transformations- / Montagezeit 100-120 min


