

TRK-MFD

TRANSFORMER/RELAIS KIT

The TRK-MFD kit consists of a transformer with thermal relay to be mounted in a mobile welding fume extractor type MFD in case a working light or working light with automatic/start stop is installed in the hood of the connected extraction arm.





 7x

SPECIFICATIONS

■ Physical dimensions and properties	
Dimensions:	
• transformer	• 95 x 60 x 58 mm (3.7 x 2.4 x 2.3 in.)
• relay	• 45 x 47 x 55 mm (1.8 x 1.9 x 2.2 in.)
Weight (net)	1,3 kg (2.9 lbs)
■ Electrical data	
Power consumption	50 W
Connection voltage	24 V
Fuse	2,0 A-T
■ Ambient conditions	
Storage conditions	• 5-45°C (41-113°F) • relative humidity max. 75%
■ Product combinations	
• WL • NCW-4 • (Ultra)Flex-3/4 • MFD	• working light • connection wire • extraction arm • mobile welding fume extractor
• WL+AST • NCW-4 • (Ultra)Flex-3/4 • MFD	• working light + automatic start/stop • connection wire • extraction arm • mobile welding fume extractor
■ Scope of supply	
Fully premounted and wired TRK-MFD (transformer, relay and fuse holder with fuse and connection block) - mounting bolt (7)	
■ Order information	
Article number	9820300030
Number/package	1
■ Shipping data	
Gross weight	1,5 kg (3.3 lbs)
Packing dimensions	33 x 22 x 6,5 cm (13 x 8.7 x 2.6 in.)
Harmonized Tariff Code	8536.4900.99
Country of origin	the Netherlands

APPROVALS/CERTIFICATES

	
	Directive 2011/65/EC (RoHS) valid as of 8 June 2011

Product type	TRK-MFD
Article no.	9820300030
Product category	Control equipment
Version	080212/B

Always check the latest version on www.plymovent.com.