



MODEL 125

125 LB. (58 kg) CAPACITY

ELECTRODE STABILIZING OVEN

OPERATING INSTRUCTIONS

&

SAFETY INFORMATION

GULLCO INTERNATIONAL LIMITED

Tel: 905-953-4140 Fax: 905-953-4138 E-mail: sales@gullco.com

GULLCO INTERNATIONAL INC U.S.A

Tel: 440-439-8333 Fax: 905-953-4138 Email: ussales@gullco.com

GULLCO INTERNATIONAL (U.K.) LIMITED EUROPE

Tel: +44 1257 253 579 Fax: +44 1257 254 629 Email: sales@gullco.co.uk

GULLCO INTERNATIONAL PTY LIMITED AUSTRALIA

Tel: 61 (0) 7 5439 0701 Fax: 61 (0) 7 5439 0704 Email: ausales@gullco.com

GULLCO INTERNATIONAL LIMITED INDIA

Tel: 91 (20) 4272212 Fax: 91 (20) 4272212 Email: india.lo@gullco.com

125 LB CAPACITY ELECTRODE STABILISING OVEN- - OPERATING INSTRUCTIONS

Model:	125
Capacity:	125 lbs / 58 kg
Voltage:	110 or 220 Volts 50 HZ 1 Phase (See Rating Plate)
Wattage:	1000 Watts at 115 v. 750 Watts at 200 v.
Range:	100- 550° F. 38-288°C
Weight:	55 Lbs. / 25kg
Dimensions:	H- 16": W- 16": D- 24½" External H-406mm, W-406mm, D- 622mm External H- 8¼": W- 9¾": D- 19" Internal H-209mm, W-247mm, D-483mm Internal

THE FOLLOWING INSTRUCTIONS AND SAFETY WARNING MUST BE READ BEFORE THIS EQUIPMENT IS CONNECTED AND PLACED INTO SERVICE

BEFORE CONNECTION ENSURE THAT SUPPLY VOLTAGE MATCHES THAT SHOWN ON THE RATING PLATE
The Model 125 is an insulated 125 lb (58 kg) capacity Electrode Stabilising Oven, generally located in the storage area and used to either maintain the electrodes in their dry state or dry out electrodes that have picked up moisture. It is complete with controls recessed for protection removable shelves to accommodate large loads, full insulation to prevent heat loss, pilot light to indicate oven operation and a heating system incorporating 1000 watts of low density elements. Temperature thermostatically controlled with a range of 100 to 550° (38-288°C) F. Nesting feet and sockets ensure safe, easy stacking.

Care must be taken to ensure that there is adequate free space around the oven to allow safe loading and discharge of the load. It is essential that any user of this equipment takes all precautions when loading and discharging the hopper. Eye protection, protective gauntlets, overalls and protective footwear should be used at all times.

During use, the load and certain parts of the equipment may be heated to temperatures rising to 550°F. (288°C) All exposed parts of the body must be adequately earthed. Before any attempt is made to remove any covers the supply must be isolated and precautions taken to ensure that it cannot be restored whilst the unit is being worked on.

USING THE OVEN

The oven is loaded via the front door. Care must be taken to avoid contact with hot surfaces during this operation. The load should be distributed safely and evenly within the oven, using the shelves provided, to ensure even heating of the electrodes. The shelves may be removed, if required, to accommodate larger loads.

Heating times may vary according to the ambient temperature at which the electrodes were stored prior to loading. An optional thermometer kit (Model T23) can be fitted to indicate the oven temperature.

REPLACEMENT PARTS FOR MODEL 125 LB OVEN

1014	Element 115 volt- 1000 watt
*1014A	Element 220 Volt-750 watt
EA-5	Thermostat with knob
EA-5K	Thermostat knob
1010A1	Pilot Light, 115 volt
*1090-G1	Pilot Light, 220 volt
1017-28N	Door Latch, complete
10LC	Line Cord
T23	Thermometer Kit
1029-5	Thermometer only
*- For 220 Volt Model	

SCHEMATIC

